

February 2009

C901

Smile Cyber-shot™







Preface

Purpose of this document

This White paper will be published in several revisions as the phone is developed. Therefore, some of the headings and tables in this document contain limited information. Additional information and facts will be forthcoming in later revisions.

The aim of this White paper is to give the reader an understanding of the main functions and features of this phone.

People who can benefit from this document include:

- Operators
- Service providers
- Software developers
- Support engineers
- Application developers

This White paper is published by:

Sony Ericsson Mobile Communications AB, SE-221 88 Lund, Sweden

www.sonyericsson.com

© Sony Ericsson Mobile Communications AB, 2008. All rights reserved. You are hereby granted a licence to download and/or print a copy of this document.

Any rights not expressly granted herein are reserved.

First edition (February 2009)
Publication number: 1220.9861 R1A

This document is published by Sony Ericsson Mobile Communications AB or its local affiliated company, without any warranty*. Improvements and changes to this text necessitated by typographical errors, inaccuracies of current information or improvements to programs and/or equipment, may be made by Sony Ericsson Mobile Communications AB at any time and without notice. Such changes will, however, be incorporated into new editions of this document. Printed versions are to be regarded as temporary reference copies only.

*All implied warranties, including without limitation the implied warranties of merchantability or fitness for a particular purpose, are excluded. In no event shall Sony Ericsson or its licensors be liable for incidental or consequential damages of any nature, including but not limited to lost profits or commercial loss, arising out of the use of the information in this document.

Sony Ericsson Developer World

At www.sonyericsson.com/developer, developers find the latest technical documentation and development tools such as phone White papers, Developers guidelines for different technologies, Getting started tutorials, SDKs (Software Development Kits) and tools plugins. The Web site also features news articles, moderated discussion forums offering free technical support and a Wiki community sharing expertise and code examples.

For more information about these professional services, go to the Sony Ericsson Developer World Web site.

Document history

Change history		
2009-02-09	Version 1	First version

Contents

Product overviewProduct overview	5
Key features	6
Images	8
Technologies in detail	9
·	
Facts and figures	
Technical specifications	
General technical data	
Performance and technical characteristics	
USSD technical data	
GPRS technical data	
SIM AT services supported	
Entertainment	
Audio and Video	
Java™	
Imaging/Messaging	
5 megapixel camera	
Video telephony	36
Images	36
Supported character set	37
Short Messaging Service	37
Enhanced Messaging Service	39
Multimedia Messaging Service	40
Email client technical data	42
Connectivity	43
Bluetooth™ wireless technology technical data	43
OMA Data Synchronization (SyncML™) technical data	44
Microsoft® Exchange ActiveSync®	
Web browser technical data	45
Client Provisioning	48
Abbreviations	50
Related information	54
Documents	
Links	54
Trademarks and acknowledgements	

Product overview

C901 is a stick Cyber-shot[™] phone that offers both refreshing industrial design and the latest Cyber-shot applications. It has a 5 megapixel camera, Xenon flash and a wide range of imaging features which make taking great pictures easy and fun. For example, C901 will move the area of focus to your subject's face and when the person smiles, it captures the moment. There is also an application inside which lets you order photo prints to be printed and sent to your door. Enjoy this mobile mutimedia device with a focus.

Features include:

- 5 megapixel camera with face detection, Xenon flash, Smile shutter and Smart contrast.
- Easy-to-use horizontal digital camera menu with illuminated icons for settings shortcuts.
- Photo fix to improve an under-exposed photo immediately.
- 2.2-inch QVGA scratch resistant mineral glass screen.
- Automatic blog creator
- The ability to share images using mobile blogging.
- · Video blogging.
- Web browser supporting HTML.
- Dynamic Web pointer for Web browsing.
- PictBridge[™] to print photos directly on a printer.
- Slide shows with music, transitions and more.
- 3D gaming.
- Web feeds.
- Web feeds ticker in standby.
- FM radio with RDS and TrackID™.

- Exchange ActiveSync®
- Accelerometer to support auto-rotated browsing and UI, and motion gaming

Key features

5 megapixel camera

The main camera is 5 megapixel and includes auto focus,16x digital zoom, Xenon flash, red-eye reduction, BestPic[™], Auto rotate, Face detection, Smile Shutter[™] and Photo fix. All this means high quality photos. The Photo light can be used as video light when recording videos. The camera is protected by a lens cover. The horizontal user interface allows for easier camera handling. A photo can be shared as a picture message, email message or blog with friends or family. Photos can also be transferred to another phone or computer using any available transfer method, such as Bluetooth[™] wireless technology or USB cable.

2.2-inch QVGA screen

The large 2.2-inch (240x320 pixels) full graphic QVGA 262k colour screen enhances viewing, facilitating high-quality multimedia and entertainment.

BestPic[™]

A unique function for Sony Ericsson camera imaging. Taking a single photo or even a burst of photos does not always catch the moment, which may have been just before or just after the camera key was pressed. BestPicTM is designed to solve this problem. Press the camera key half way down and the camera starts capturing photos. Press the key fully down, and nine photos appear automatically. The photos range from left (just before pressing the camera key fully down) to centre (camera key fully down) to right (just after pressing the camera key fully down). The centre photo is the default photo, but not necessarily the best one. Browse the photo series and save the best photos.

Auto rotate

Auto rotate is a new feature, which enables HB108 R1.1 to register how the phone is oriented when the photo is taken, whether it is held in portrait or landscape mode. This information is saved with the photo. When viewed, the photo is automatically rotated and presented in the same orientation as it was originally taken. The same technology which makes this possible also enables you to switch between horizontal and vertical viewing when exploring the media and browsers simply by turning the phone.

Video camera

The camera captures a video recording and saves it in the phone or on a memory card. A video clip can be posted online or shared as a picture message or email with friends and family.

Web feeds

A built-in RSS (Really Simple Syndication) Reader is used in combination with the Internet browser. When browsing, frequently updated content such as news headlines or podcasts can be received as feeds.

HTML Web browser support

You can browse the Internet and look at Web sites in a different way with the Access NetFront™ 3.4 – an HTML browser which supports a complete Web standard suite.

Mobile blogging

You can send photos and video clips using the Internet to show on your personal blog or other Web site, allowing people easy access to view and comment on your photos and video clips.

Photo tags

Navigate through your captured photos and thousands of downsized photos transferred from your computer. View captured photos and video clips in an intuitive timeline view. Play animated slide shows with music and different moods. Tag your photos to find them faster. The built-in sensor in the camera ensures that all photos are rotated correctly.

PictBridge™ - Camera printing

Print photos from the phone using a USB cable connected directly to a printer, without a computer or photo editing software.

Push email

The phone supports push email, a method of pushing new email messages automatically to mobile devices. Push email increases mobile email usability by delivering email in the background (similar to SMS or MMS), eliminating the need for the user to manually check for new email.

Media

A unique Sony Ericsson media experience. All media can be accessed directly from the desktop. You can navigate easily through captured photos and video clips, pictures, photo tags, music, videos and more. If you are browsing your media in vertical position and wish to change to horizontal, simply turn the phone to the horizontal position.

PlayNow™ 5.0

A unique and easy-to-use direct-link for downloading ringtones, full track music, games, themes and wallpapers. PlayNow™ offers best-selling content for mobile download. Users can preview content before purchase. Users have access to a catalogue of millions of tracks from both international and local labels.

By combining the PlayNowTM catalogue with unique applications like TrackIDTM users are presented with a My TrackIDTM list and TrackIDTM Charts by country, created by TrackIDTM users around the world. These charts are based on what songs other users are searching for and want to hear the most. PlayNowTM supports MP3 and Windows Media DRM file formats for music.

TrackID™

TrackIDTM enables the user to identify a track playing on the built-in radio, or a track playing in the room. A few seconds of the song is sampled, the phone connects to an online database, which identifies the song and returns title, artist and album information.

Bluetooth™ wireless technology

Several devices (simultaneous Bluetooth™ wireless technology connections) can be connected up to 10 metres (33 feet) away using Bluetooth wireless technology. For example, when the phone rings, it can be answered with a Bluetooth headset, and images can be sent to another phone at the same time. Several mobile phones can take part in a Bluetooth wireless technology-supported game and the phone and a computer can exchange data such as images, video clips, vCards, music files and calendar data. Bluetooth wireless technology version 2.0 and Enhanced Data Rate (EDR) are supported.

USB 2.0 mass storage

When connecting the phone to a computer using a USB cable, the memory in the phone appears on the computer screen as a removable disk along with other disks and drives in the computer. You can then quickly and easily drag and drop items such as images, documents, music and video clips between folders in the phone and the computer.

Images



















Technologies in detail

The following includes short descriptions of the technologies available in C901 Cyber-shot™ and C510 Cyber-shot™.

Feature	C901Cyber-shot™	C510 Cyber-shot™
3D games	Yes	Yes
3G enabled	Yes	Yes
Activity menu (multi-tasking) The user can easily handle missed calls, new text and picture messages, task reminders, shortcuts and get quick access to favourite Internet bookmarks	Yes with enhanced functionality for background applications	Yes with enhanced functionality for background applications
Alarm clock The user can set up to five individual times for single or recurring weekly alarms. It is also possible to adjust the snooze interval.	Yes	Yes
Auto rotate When viewing photos, video clips or browsing the Web, you can switch between portait and landscape mode by simply rotating the phone.	Yes	Yes
Backlight White backlight to illuminate the phone screen	Yes	Yes

Feature	C901Cyber-shot™	C510 Cyber-shot™
Battery	BST-33 3.6 V, 950 mAh, Lithium Polymer	BST-38 3.6 V, 930 mAh, Lithium Polymer
Battery charging time	At least 90% charged within 2 hours. Fully charged within 2.5 hours	At least 90% charged within 2 hours. Fully charged within 2.5 hours
BestPic™	Yes	No
Enhance photo taking by automatically capturing a series of photos ranging from nine before to after a camera key press. Select the best photo to catch the moment. You can also save several or all photos.		
Bluetooth™ audio streaming	Yes	Yes
The user can listen to audio in Bluetooth™ A2DP compatible devices		
Bluetooth™ audio video remote control	Yes	Yes
Ther user can control music player functions from a Bluetooth™ accessory, and control the volume in the accessory from the phone		
Bluetooth™ PAN	Yes	Yes
The user can connect the phone to Internet using Bluetooth™ wireless technology		
Bluetooth™ wireless technology	Yes	Yes
Wireless connectivity between devices within a range of up to 10 metres (33 feet). Support for specification of the Bluetooth System, version 2.0 and EDR		
Business card exchange	Yes	Yes
The user can exchange contact information		
Buy Now	Yes	Yes
Mark a track if you are interested in buying it later. Option to buy the track when synchronising with Microsoft® Windows Media® Player. The Buy Now service requires a subscription and account with a downloadable music service, a computer with Microsoft® Windows Media® Player 11 or subsequent compatible version of Windows Media® Player, and a USB computer connection		

C901Cyber-shot™	C510 Cyber-shot™
Yes	Yes
Yes	Yes
Yes	Yes
5 megapixel	3.2 megapixel
Yes	Yes
Yes Xenon flash	Yes
Yes, only for video	No
recording	
Yes	Yes
Yes	Yes
Yes	Yes
	Yes Yes Yes 5 megapixel Yes Yes Yes Yes Yes Yes Yes Ye

Feature	C901Cyber-shot™	C510 Cyber-shot™
Camera mode switch	Yes	No
A dedicated key to switch between still and video camera		
Camera red eye reduction	Yes	No
Camera scene modes Predefined settings when taking photos in different environments, for example, at night or of fast-moving objects	Yes Dedicated key for scenes	Yes Dedicated key for scenes
Camera settings bar	Yes	Yes
Settings bar with options and info texts		
Chinese input method	Yes	Yes
Chinese input methods: Text input methods based on Simplified or Traditional Chinese. Bopomofo, Pinyin or Stroke		
Co-branding area	39.76 x 5.3 mm	20 x 6.4 mm
Code memo	Yes	Yes
A safe place to save all PIN codes and other information. To access Code memo, only one PIN code is needed		
Colour	Noble Black Precious Peach Sincere Silver	Future black Radiation Silver
Contact photos	Yes	Yes
You can add a photo to a saved contact. The picture appears on the screen when the saved contact calls		
Contacts	Yes	Yes
Phonebook with fields for name, phone, fax and instant messaging information, presence information, email address, Web site, title, company address info, personal address info and birthday		
Conference calls	Yes	Yes
Support for multiparty calling		
Connector A1 (Fast port)	Yes (side)	Yes (side)

Feature	C901Cyber-shot™	C510 Cyber-shot™
Content online	Yes	Yes
Downloadable pictures, games, themes, ringtones available online		
Copyright protection DRM (Digital Rights Management) features the rights and copy protection of downloaded content (audio, pictures, music tones, video clips and entertainment features such as games, Java applications and other content.)	Yes, OMA DRM 1.0, 2.0 and 2.1, Microsoft DRM Janus	Yes, OMA DRM 1.0, 2.0 and 2.1, Microsoft DRM Janus
Device Management (DM)	Yes	Yes
DM utilises GPRS as a bearer (basic network connectivity needs to be in place) of the provisioning data and allows the operator to access the phone, check and send out different settings such as network connectivity (GPRS), email, MMS, Internet settings and Java™. Device Management is achieved by supporting OMA Client Provisioning 1.1 (CP) and OMA Device Management (DM) 1.2		
Digital zoom	16x for all photo sizes and video recording	16x for all photo sizes except big sizes and video recording
Email	Yes	Yes
Built-in email client with inbox, outbox, compose/ send and other functions		
EMS (Enhanced messaging)	Yes	Yes
Text messaging (SMS) with support for pictures and sounds		
Note: EMS is not available for operators who use unified messaging		
Exterior description	105.6 x 45 x 13.2 mm	107 x 46.6 x12.5
Size (Length x width x thickness/thinnest)	100.0 A 40 A 10.2 IIIII	(mm)
Fast port	Yes	Yes
A system connector which enables faster data transfer between the phone and a computer		

Feature	C901Cyber-shot™	C510 Cyber-shot™
File manager Folder structure storage to help save and organise pictures, sounds and other phone content	Yes, with enhanced functionality for camera content	Yes, with enhanced functionality for camera content
Flash themes	Yes	Yes
Flight mode	Yes	Yes
All phone radio transceivers are inactivated. Flight mode starts the phone so that only certain functions are available, such as the calendar, the music player or a game. The phone may then be used in some areas, such as aeroplanes or hospitals, where full mobile phone functionality is not allowed Bluetooth™ wireless technology function availability in Flight mode	Yes	Yes
FM radio with RDS FM radio with presets, auto and manual search. The handsfree is used as an antenna. The radio can also be used as an alarm signal	Yes, 100 kHz tuning interval	Yes, 100 kHz tuning interval
FM radio with TrackID™	Yes	Yes
Identify tracks playing on the radio		
Form factor	Stick	Stick
Games download	Yes	Yes
The user can add more games to the phone		
Games embedded	Yes	Yes
Geo tagging Photos are tagged with geo data and can be shown on a map	Yes, geo data from cell ID	Yes, geo data from Cell ID
Google Maps™ for mobile	Yes	Yes
Preloaded application with support for cell-id and GPS. The user can view satellite imagery, find locations and calculate routes		

Feature	C901Cyber-shot™	C510 Cyber-shot™
GPRS	Yes	Yes
General Packet Radio Services - a communications standard enabling packet data transfer of 21.4 Kbps per time slot. Multislot class 10 supported (max 5 simultaneously)		
High Speed Data		
HSDPA - High Speed Downlink Packet Access HSUPA - High Speed Uplink Packet Access	Yes Yes	Yes Yes
Icon Desktop 12	Yes	Yes
A graphic icon desktop with 12 interactive icons		
Image formats		
8 MP (3264x2448 pixels)	No	No
5 MP (2592x1944 pixels)	Yes	No
3.2 MP (2048x1536 pixels)	No	Yes
3 MP (2048x1536 pixels)	Yes	No
VGA (640x480 pixels)	Yes	Yes
		Yes
		Yes
Instant messaging (Wireless Village™)	Yes	Yes
Chat – several people can take part in a mobile messaging session. Instant messaging/Wireless Village server community		
Internet blogging	Yes	Yes
The user can share over the Internet on a personal Web site. The size of uploaded photos is dependent on customisations		

Feature	C901Cyber-shot™	C510 Cyber-shot™
Internet browser	Yes	Yes
Full HTML support, ECMA script, DOM level 1&2, CSS 1&2 and so on.	Yes	Yes
Support for AJAX (Asynchronous JavaScript and XML)	Yes	Yes
Progressive download of video files	Yes	Yes
Direct access to Bookmarks, Search Internet and Enter address Mouse Pointer	Yes Yes	Yes
Text Wrapping	Yes	Yes
Pan&Zoom	Yes	Yes
Internet security	Yes, SSL/TLS	Yes, SSL/TLS
Encrypts confidential information such as credit card and bank account numbers. Necessary for mobile banking and shopping		
Java TM	Java 2, Micro Edition (J2ME™), Java 3D™	Java 2, Micro Edition (J2ME™), Java 3D™
Support for J2ME™ technology	JP-8.4	JP-8.4
Sony Ericsson Java Platform	Yes	Yes
Support for new Java programming features including banking, payment transactions, user identification and authentication through secure encryption technology		
Keys - navigation and more	4 navigation keys	4 navigation keys
	3 selection keys	3 selection keys
	C (Clear) key	C (Clear) key
	Activity menu key	Activity menu key
	End and on/off key	End and on/off key
	Call key	Call key
Keys - keypad	12 alphanumeric	12 alphanumeric

Feature	C901Cyber-shot™	C510 Cyber-shot™
Keys - side and other	Volume/camera zoom key	Volume/camera zoom key
	Camera key	Camera key
	Camera mode key	
	Camera view key	
Lunar calendar	Yes	Yes
A calendar system used in China and other parts of Asia. A lunar month is determined by the period required for the moon to complete its full cycle of 29.5 days and is available in Chinese phone variants		
Adobe™ Flash Lite™	Yes	Yes
For animated wallpapers, menus and other graphic elements		
Media	Yes	Yes
A centre for all media content with horizontal and vertical navigation. You can view photos, listen to music, watch video clips. If you are browsing your media in vertical position and wish to change to horizontal, simply turn the phone to the horizontal position.		
Media player	See Music player and Video player	See Music player and Video player
Mega Bass™	Yes	Yes
An audio feature which enhances bass frequencies for better overall music experience		
Memory (built-in)		
Phone memory that is free to use (depending on software configuration and file content). Many applications share phone memory. The maximum amount of storage available for any one application, such as calendar entries, is affected by the amount of memory used by other applications, such as messaging, music, photos and so on	Up to 110 MB	Up to 120 MB

Feature	C901Cyber-shot™	C510 Cyber-shot™
Memory card reader (slot)		
A slot for inserting a micro peripheral storage device	Yes	Yes
Memory card support: Memory Stick Micro [™] (M2 [™]) SanDisk microSD [™] /Transflash [™]	Yes No	Yes No
Menu layout options	Yes	Yes
Possibility to change the layout of the icons in the main menu		
Menu shortcuts	Yes	Yes
A function making it possible to dedicate shortcuts to the most-used phone functions		
MMS (Multimedia messaging)	Yes	Yes
Picture messaging with text and sound		
MMS video	Yes	Yes
Support in the phone for sending video clips using MMS		
Modem	Yes	Yes
Circuit Switched/Packet Switched Internet dial-up support		
MusicDJ™	Yes	Yes
A music composer tool with MIDI drum, guitar, keyboard, bass and brass loops in different music styles, which can be combined to create polyphonic ringtones		
Music listening time	Up to 25 hours	Up to 20 hours
Music player 3.0	Yes	Yes
A digital music player with horizontal navigation. The user can play transferred or downloaded music. The list structure lets the user, for example, organise favourite songs into groups and create simple playlists		
Music tones	Yes	Yes
Music tones, also called master tones, are DRM protected music by original artists. Various digital audio formats are supported		

Feature	C901Cyber-shot™	C510 Cyber-shot™
Networks		
Variant 1 UMTS/HSUPA/HSDPA 850, 1900, 2100 GSM/GPRS/EDGE 850, 900, 1800, 1900	Yes	Yes
Variant 2 UMTS/HSUPA/HSDPA 900, 2100 GSM/GPRS/EDGE 850, 900, 1800, 1900	Yes	Yes
Variant 3 GSM/GPRS 850, 900, 1800, 1900	Yes	
Notes	Yes	Yes
The user can make notes of things to remember. A note can be shown in standby		
OMA Data Synchronization (SyncML)	Yes	Yes
A device communications standard that enables remote synchronization between devices	OMA DS 1.2 OMA DS 1.1.2	OMA DS 1.2 OMA DS 1.1.2
OTA settings	Yes	Yes
Internet, email and other settings can be sent over the air to the phone	OMA CP 1.1	OMA CP 1.1
PhotoDJ™	Yes	Yes
A drawing tool in the phone where existing photos can be altered		
Photo fix	Yes	Yes
Improves an under-exposed photo by calculating and adjusting the light balance		
PictBridge™	Yes	Yes
The user can transfer images from the phone via a USB cable directly to a printer, without a computer or photo editing software		
Picture gallery	Yes	Yes
A thumbnail image gallery where sections of several photos can be viewed at the same time	Use photo tags	Use photo tags

Feature	C901Cyber-shot™	C510 Cyber-shot™
PlayNow™ (direct link)	Yes	Yes
You can listen to music before you purchase and download it to your phone		
PlayNow™ Games (direct link)	Yes	Yes
You can download and purchase games straight from the phone desktop		
Polyphonic voices	72	72
Powersave	Yes	Yes
A default setting for display light		
Predictive text input	Yes	Yes
Push email	Yes	Yes
RSS reader	See Web feeds	See Web feeds
Screen		
Type: Size:	Full graphical 2.2 inches	Full graphical 2.2 inches
Resolution:	240x320 pixels	240x320 pixels
Technology: Colours displayed together:	TFT, QVGA 262,000 (18 bit)	TFT, QVGA 262,000 (18 bit)
Backlight colour:	White	White
Screen saver	Yes	Yes
Settings download (Ready to run)	Yes	Yes
The user can set up functions that require a connection to the Internet such as the Internet browser and picture messaging. This function runs in the setup wizard or can also be chosen in the Settings menu. This function is not included in the setup wizard for customised phones		
Shake control	No	No
Shake control for music and gaming		
SIM card lock	Yes	Yes
The possibility to protect the SIM card with a four-digit to eight-digit PIN code		

Feature	C901Cyber-shot™	C510 Cyber-shot™
Smart search	Yes	Yes
You can search for numbers and contacts from standby by using the number keys. You can filter and search by names in contacts list by entering some keys. You can call or send messages from a filtered list of search results.		
SMS long (Text messaging)	Yes	Yes
Concatenated SMS text messaging		
Sleep mode	Yes	Yes
A power-saving feature that minimises the battery power consumed when the phone is in standby		
Sony Ericsson Remote Update Service	Yes	Yes
The user can download the latest software over the air		
Sony Ericsson Update Service	Yes	Yes
The user can connect the phone to an Internet- connected computer, download the latest software from , <u>www.sonyericsson.com/support</u> and update the mobile device		
Sony Ericsson Update Service Pro	Yes	Yes
The user can update the phone with the latest software at alocal Sony Ericsson retailer		
Sound recorder	Yes	Yes
A recording device in the phone that can record voice messages or other sounds		
Speakerphone	Yes	Yes
Speed dialling	Yes	Yes
The user can allocate contacts in the phone book to specific keys on the keypad		
Standby time	Up to:	Up to:
GSM UMTS	400 hours 350 hours	400 hours 400 hours
Status view	Yes	Yes
The screen shows the network being used, the time and other status information		

Feature	C901Cyber-shot™	C510 Cyber-shot™
Stereo speakers	No	Yes
Stopwatch	Yes	Yes
SVG Tiny	Yes	Yes
Scalable Vector Graphics for impressive animated wallpapers, menus and other graphic elements		
Synchronisation PC	Yes	Yes
The user can synchronise and share phone content with a computer		
Talk time	Up to:	Up to:
GSM UMTS	10 hours 4 hours	10hours 2.5 hours
Tasks	Yes	Yes
Keeps track of important things you have to do		
Themes	Yes	Yes
Phone menu texts and background graphics		
Timer	Yes	Yes
You can set the phone to alert after a specific time		
TrackID™		
Music recognition	Yes	Yes
You can text search for artist, album, track, lyrics and other information.	Yes	Yes
UMTS	Yes	Yes
USB connectivity support	Yes	Yes
You can connect the phone to a computer using the USB cable provided	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
USB ethernet emulation	Yes	Yes
You can connect to the Internet using the phone or a computer		
Vibrating alert	Yes	Yes
The phone vibrates when a call comes in		

Feature	C901Cyber-shot™	C510 Cyber-shot™
Video blogging	Yes	Yes
The user can share video clips over the Internet on a personal Web site. The size of uploaded video clips is dependent on customisations		
VideoDJ™	Yes	Yes
The user can create video sequences by combining different clips and adding music and images		
Video player	Yes	Yes
The user can play transferred or downloaded video clips. The user can ransfer video clips to another phone or a computer using an available transfer method		
Video streaming	Yes	Yes
Real-time streaming of video clips, for example, live cam. Media can also be downloaded and saved in the phone memory		
Viewfinder	Yes	Yes
When using the camera, a photo can be previewed before it is captured		
Voicemail	Yes	Yes
Support for voicemail operator service including automatic answering and message recording		
Web feeds	Yes	Yes
Frequently updated content delivered as feeds via a Web site, for example, news headlines in the browser		
Web feeds ticker	Yes	Yes
The user can view news headers in standby		
Weight	105 g	91.5 g

Facts and figures

This chapter offers readers a detailed listing of all the technical data relating to the product. Comprehensive descriptions of performance and technical characteristics are presented in table format for quick and easy access.

Technical specifications

General technical data

System	Quad-band GSM Release 5 recommendations, GSM 850, GSM 900, e-GSM 900, GSM 1800, GSM 1900 Tri band UMTS/HSDPA 850, 1900, 2100 supported
Speech coding	HR, FR, EFR, AMR, supported where available, for high speech quality
GSM SIM/ UMTS USIM/SIM card	GSM SIM - 3GPP TS 51.011; UMTS USIM - 3GPP TS 31.102; UMTS ISIM - 3GPP TS 31.103. Small plug-in card, 1.8 V and 3 V
Memory	Up to 160 MB internal (depending on software configuration/file content) plus extra slot for supported memory cards
Data transfer speeds	Up to 7.2 Mbps (downlink, HSDPA, cat 8) Up to 384 Kbps (uplink, WCDMA R99)

Performance and technical characteristics

Property	WCDMA 2100
Frequency range (MHz)	TX: 1920–1980 RX: 2110–2170
Channel spacing	5 MHz with 200 kHz channel rasters
Number of channels	277
Modulation	QPSK (WCDMA R99) QPSK/16 QAM (HSDPA)
πι	10 ms (WCDMA R99) 2 ms (HSDPA)
TX phase accuracy	Error Vector Magnitude: <17.5%
Duplex spacing	190 MHz
Frequency stability	+/-0.1 ppm
Voltage operation (nominal)	3.6 V
Transmitter RF power output	24 dBm Class 3 (0.25 W peak)
Transmitter Output impedance	50 ohm
Transmitter spurious emission (according to specification)	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz (according to 3GPP™ spec.)

Property	WCDMA 2100		
Receiver RF sensitivity	Better than -106.7 dBn	Better than -106.7 dBm @ 12.2 kbps CS voice	
Receiver RX bit error rate	< 0.1%		
Property		GSM 850	GSM 900/ E-GSM 900
Frequency range (MHz)		TX: 824-849 RX: 869-894	TX: 880-915 RX: 925-960
Channel spacing		200 kHz	200 kHz
Number of channels		124 Carriers *8 (TDMA)	174 Carriers *8 (TDMA)
Modulation		GMSK	GMSK
TX phase accuracy		< 5° RMS phase error (burst)	< 5° RMS phase error (burst)
Duplex spacing		45 MHz	45 MHz
Frequency stability		+/- 0.1ppm	+/- 0.1ppm
Voltage operation (nominal)		3.6 V	3.6 V
Transmitter RF power outp	ut	33 dBm Class 4 (2 W peak)	33 dBm Class 4 (2 W peak)
Transmitter output impedance		50 ohm	50 ohm
Transmitter spurious emiss specification)	ion (according to	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz
Receiver RF sensitivity		Better than -104 dBm	Better than -102 dBm
Receiver RX bit error rate		< 2.4%	< 2.4%
Property		GSM 1800	GSM 1900
Frequency range (MHz)		TX: 1710-1785 RX: 1805-1880	TX:1850-1910 RX:1930-1990
Channel spacing		200 kHz	200 kHz
Number of channels		374 Carriers *8 (TDMA)	299 Carriers *8 (TDMA)
Modulation		GMSK	GMSK
TX Phase Accuracy		< 5° RMS Phase error (burst)	< 5° RMS Phase error (burst)
Duplex spacing		95 MHz	80 MHz
Frequency stability		+/-0.1ppm	+/-0.1ppm
Voltage operation (nominal))	3.6 V	3.6 V
Transmitter RF power outp	ut	30 dBm Class 1 (1 W peak)	30 dBm Class 1 (1 W peak)

Property	GSM 1800	GSM 1900
Transmitter output impedance	50 ohm	50 ohm
Transmitter spurious emission (according to specification)	< –30 dBm	< –30 dBm
Receiver RF sensitivity	Better than -102 dBm	Better than -102 dBm
Receiver RX bit error rate	< 2.4%	< 2.4%

USSD technical data

Feature	Support
USSD support	GSM Phase 1/2 (cross-phase compatibility)
Mode support	UI-mode supportedSAT initiated USSD supported
UI-mode details	 It is possible to scroll the text up and down in USSD messages It is possible to highlight embedded numbers and take actions accordingly

GPRS technical data

Property	Support
Compatible GPRS/EDGE and SMG specifications	Release 99 according to ETSI specification
Data rates GPRS (per time slot)	Coding scheme
	CS-1: 9 Kbps
	CS-2: 13,4 Kbps
	CS-3: 15,6 Kbps
	CS-4: 21,4 Kbps (network-dependent).
Data rates EDGE (per time slot)	Modulation & coding scheme (MCS)
	MCS-1 (GMSK): 8.0 Kbps
	MCS-2 (GMSK): 11.4 Kbps
	MCS-3 (GMSK): 14.8 Kbps
	MCS-4 (GMSK): 17.6 Kbps
	MCS-5 (8-PSK): 22.4 Kbps
	MCS-6 (8-PSK): 29.4 Kbps
	MCS-7 (8-PSK): 44.8 Kbps
	MCS-8 (8-PSK): 54.4 Kbps
	MCS-9 (8-PSK): 59.2 Kbps
Medium Access Modes	Dynamic allocation
Support of Packet Control Channels (PBCCH/PCCCH)	Yes
Network operation mode	NOM I, II, III

Property	Support
Support of GPRS/CS combined procedures	Yes
Network control mode	NC0 and NC2
Support of access in 2 phases	Yes
Support of PRACH on 11 bits	Yes
Support of GPRS re-selection C31/C32	Yes
Support of static and dynamic addressing	Yes
Support of power control uplink and downlink	Uplink = yes, downlink is a network feature
Support of ciphering algorithms	GEA1, GEA2
Support of compression algorithms	Yes, V42bis and IP header compression
Mode of operation	Class B and Class C modes of operation supported
R Reference point	 Physical layer: Support of RS232 PPP is supported as L2 layer in the R reference point Authentication algorithms PAP, CHAP supported
IP connectivity	 PDP type IP is supported IP termination in mobile or TE (laptop, PDA) is supported
PDP context	 10 PDP context descriptions saved in the phone PDP context description is edited via application in the phone AT-command or via OTA Simultaneous PDP contexts are supported, maximum 4
SIM	GPRS aware, as well as non-GPRS aware, SIM cards are supported
AT commands	Some of the supported commands: AT+CGDCONT - DEFINE PDP CONTEXT AT+CGEQREQ - Quality of Service Profile (REQUESTED) AT+CGEQMIN - Quality of Service Profile (Minimum Acceptable) AT+CGATT - PACKET DOMAIN SERVICE ATTACH OR DETACH AT+CGACT - PDP CONTEXT ACTIVATE OR DEACTIVATE AT+CGDATA - ENTER DATA STATE For more information, see www.sonyericsson.com/developer

SIM AT services supported

Service	Mode	Support
CALL CONTROL BY SIM		Yes
MO SMS CONTROL		Yes

Service		Mode	Support
DATA DOWNLOAD TO SIM		Cell Broadcast SMS	Yes Yes
DISPLAY TEXT		Text of up to 240 characters (120 UCS2 coded).	Yes
	bit 1:	0 = normal priority	Yes
		1 = high priority	Yes
	bit 8:	0 = clear message after a delay	Yes
		1 = wait for user to clear message	Yes
GET INKEY		General: The GET_INKEY requires that the user confirms his/her choice	Yes
	bit 1:	0 = digits (0-9, *, # and +) only	Yes
		1 = alphabet set	Yes
	bit 2:	0 = SMS default alphabet	Yes
		1 = UCS2 alphabet	Yes
	bit 3:	0 = character sets defined by bit 1 and bit 2 are	Yes
		 enabled 1 = character sets defined by bit 1 and bit 2 are disabled and the Yes/No response is requested 	Yes
GET INPUT		General: No. of hidden input characters	252
	bit 1:	0 = digits (0-9, *, # and +) only	Yes
		- 1 = alphabet set	Yes
	bit 2:	0 = SMS default alphabet	Yes
		1 = UCS2 alphabet	Yes
	bit 3:	0 = ME may echo user input on the display	Yes
		1 = user input not to be revealed in any way (see note)	Yes
	bit 4:	0 = user input to be in unpacked format	Yes
		1 = user input to be in SMS packed format	Yes
	bit 8:	0 = no help information available	Yes
		1 = help information available	Yes
LAUNCH BROWSER			Yes
MORE TIME			Yes
PLAY TONE			Yes
POLLING OFF			Yes
POLL INTERVAL			Yes

Service		Mode	Support
PROVIDE LOCAL INFORMATION		'00' = Location Information (MCC, MNC, LAC and Cell Identity)	Yes
		'01' = IMEI of the ME	Yes
		'02' = Network Measurement results	Yes
		'03' = Date, time and time zone (DTTinPLI)	Yes
		'04' =Language setting	Yes
		'05' =Timing advance	Yes
REFRESH		General: The reset option requests the user to wait while the phone restarts	Yes
		'00' = (U)SIM Initialization and Full File Change Notification	Yes
		'01' = File Change Notification	Yes
		'02' = (U)SIM Initialization and File Change Notification	Yes
		'03' = (U)SIM Initialization	Yes
		'04' = (U)SIM Reset	Yes
		'05' = USIM Application Reset	Yes
		'06' = 3G Session Reset	Yes
SELECT ITEM			Yes
SEND DTMF			Yes
SEND SHORT MESSAGE	bit 1:	0 = packing not required 1 = SMS packing by the ME required	Yes Yes
SEND SS			Yes
SEND USSD			Yes

Service	Mode	Support
SET UP CALL	General: Capability configuration Set-up speech call CallParty Subaddress DTMF support	Yes No Yes
	'00' = set up call, but only if not currently busy on another call	Yes
_	'01' = set up call, but only if not currently busy on another call, with re-dial	Yes
	'02' = set up call, putting all other calls (if any) on hold	Yes
	'03' = set up call, putting all other calls (if any) on hold, with re-dial	Yes
	'04' = set up call, disconnecting all other calls (if any)	Yes
_	'05' = set up call, disconnecting all other calls (if any), with re-dial	Yes
SET UP EVENT LIST	'00' = MT call	Yes
	'01' = Call connected	Yes
	'02' = Call disconnected	Yes
	'03' = Location status	Yes
	'04' = User activity	Yes
	'05' = Idle screen available	Yes
	'06' = Card reader status	Not Applicable
	'07' = Language selection	Yes
	'08' = Browser termination	Yes
	'09' = Data available	Yes
	'OA' = Channel status	Yes
SET UP IDLE MODE TEXT		Yes, 1 row of text is supported
SET UP MENU		Yes
TIMER MANAGEMENT		Yes
OPEN CHANNEL		Yes
CLOSE CHANNEL		Yes
RECEIVE DATA		Yes

Service	Mode	Support
SEND DATA		Yes
GET CHANNEL STATUS		Yes

User Interaction with SIM AT

BIP - Open Channel

A user confirmation is displayed with the default text "Open channel" when no alpha identifier is present. Alpha identifier text replaces the default text when the Alpha Identifier is present & not null. No user indication is provided (transparent mode) when alpha identifier is present and null.

Display text

Text of up to 240 characters (120 UCS coded) is supported.

Text clearing times are 5-20 seconds with a 60-second time-out limit for the user to clear the text. Key responses:

- End key Proactive session terminated by user.
- Back Backward move in proactive session.

MSK clears the screen if the command is performed successfully.

Get inkey

Prompt for a one-character input. Pressing OK without entering a character gives warning message "Text too short". Key responses:

- · C clears current character.
- End key terminates the proactive session.
- Back Backward move in the proactive session.
- OK Command performed successfully.

Get input

Prompt for character input. The phone will refuse to accept further input when maximum response length is exceeded. UI Maximum Response lengths:

- Digits Only 160 characters.
- SMS default alphabet characters 160 characters.

• Hidden Characters (digits only) – 20 characters.

Key responses:

- · C clears current character.
- End key terminates the proactive session.
- Back Backward move in proactive session.
- OK Command performed successfully.

Select item

Scroll to highlight item for selection. Key responses:

- Navigational key press down Scroll down list.
- Navigational key press up Scroll up list.
- End key terminates proactive session.
- Back Backward move in proactive session.
- OK- Command performed successfully.

Send short message

Alpha Identifier text is displayed, if it is present. Otherwise, there is no user indication if the customization for default text is not enabled. If the customization for default text is enabled, and there is no Alpha Identifier, default message "Sending message" is displayed. Default responses are "Message failed" or "Message sent" for the customization enabled case with no Alpha Identifier.

Key responses:

• End key or Back ends the proactive session.

Set up call

If you are on a call when the commands "Set up Call", "Putting all other calls on hold" are sent, the user will see the "Let SIM card setup call" user confirmation text. If OK is pressed the current call will be put on hold and the new call set up. If the phone is on a call when the command "Set Up Call, disconnecting all other calls" is sent, the user will see the "Let SIM card setup call" user information text. If the OK key is pressed the current call will be disconnected and the new call set up.

Set up menu

Incorporates a SIM Application Toolkit Menu Item into the ME's main menu structure.

If an Alpha Identifier is supplied in the Set Up Menu command, this is used as the SIM AT entry in the ME's main menu. If null alpha identifier is supplied

and several items are found in the menu, the default title "ONLINE SERVICES" is used. If the SIM AT Menu Item is selected by pressing Select, all the items sent in the Set Up Menu command will be available for selection, in the same way as the Select Item command.

Entertainment

Audio and Video

Feature	Formats	Extensions
Ringtone playback	3GP	.3gp
	AAC	.aac
	MP4	.mp4
	M4A	.m4a
	MP3	.mp3
	AMR	.amr
	AMR-WB	.awb
	WAV	.wav
	SMF (GM, GML, SP-MIDI supported)	.mid
	iMelody	.imy
	XMF (Mobile XMF/DLS supported)	.xmf, .mxmf
	WMA	.wma
Video and audio playback	MP4 (Video: MPEG4 or H.264, Audio: AAC or AAC+ or eAAC+) 3GPP™ (Video: MPEG4, H.263 or H.264, Audio: AMR-NB, AMR-WB, AMR-WB+, AAC,	.mp4
	AAC+ or eAAC+)	.3gp
	WMV	.wmv, .asf
Streaming and progressive downloading	3GPP™ PSS Rel6	
Video recording	H.263 Profile 0, Level 10	
-	MPEG-4 Visual Simple Profile Level 3	
Audio recording	AMR-NB	
G	AAC (for video recording only)	

Feature	Decoder format	Supported in file format
Video playback	MPEG-4 Visual Simple Profile H.264 Baseline Profile	3GP/MP4 3GP/MP4
	H.263 Profile 0 VC-1 (WMV9)	3GP WMV
Music playback	MPEG-1/2/2.5, audio layer 3	MP3
	AAC	3GP/AAC/MP4/M4A
	AAC+	3GP/AAC/MP4/M4A
	eAAC+	3GP/AAC/MP4/M4A
	WMA version 2, 7, 8: Class 1	WMA
	WMA version 9: Level 3	WMA
	WMA Pro (profile M0a)	WMA
	Linear/A-law/μ-law PCM	WAV

Java™

Feature	Functionalities
Java™ Platform, Micro Edition	 JSR-75 PDA Optional Packages for J2METM JSR-82 Bluetooth Wireless Technology API JSR 118 MIDP 2.0 JSR-120 Wireless Messaging API JSR-205 Wireless Messaging API 2.0 JSR-135 Mobile Media API 1.1 JSR 139 CLDC 1.1 JSR-172 J2METM Web Services Specification JSR-177 Security and Trust Services API for J2METM JSR-179 Location API (built-in GPS) JSR-180 SIP API for J2METM JSR-184 Mobile 3D Graphics API for J2METM JSR 185 JavaTM Technology for the Wireless Industry JSR-211 Content Handler API JSR-226 SVG API for J2METM JSR-229 Payment API JSR-229 Payment API JSR-234 Advanced Multimedia Supplements JSR-238 Mobile Internationalization API JSR-239 OpenGL ES JSR-248 Mobile Services Architecture JSR-256 Mobile Sensor API (accelerometer) Nokia UI Extension API
Java 3D	 Mascot Capsule Micro3D Version 3 JSR-239 OpenGL ES JSR-184 Mobile 3D Graphics API for J2ME™

Imaging/Messaging

5 megapixel camera

Digital still camera (DSC)	
True colour	Yes
Digital zoom	Main camera: 16x zoom
Photo fix	Improves an under-exposed photo by calculating and adjusting the light balance
Still camera settings bar	
Shoot modes	Normal, BestPic™, Panorama, Frames, Smile shutter, Smart contrast
Scenes	Auto, Twilight landscape, Twilight portrait, Landscape, Portrait Beach/Snow, Sports, Document
Photo sizes (resolution)	5 MP (2592x1944 pixels) 3 MP (2048x1536 pixels) 2 MP (1632x1224 pixels) 1 MP (1280x960 pixels) VGA (640x480 pixels) Note: MP = megapixel
Focus	Auto, Macro, Infinity, Face detection
Flash	Off, Auto, Red-eye reduction
ISO setting	ISO 400, ISO 200, ISO 100, ISO Auto
Self-timer	Off, On
Effects	Off, Black & white, Negative, Sepia, Solarize
White balance	Auto, Daylight, Cloudy, Fluorescent, Incandescent
Metering mode	Normal, Spot
Still camera setup	
Picture quality	Normal, Fine
Shutter sounds	Yes
Image stabiliser	No
Auto rotate	Off, On
Reset file number	Yes
Save to memory	Memory card, phone memory

Video size (resolution)	QVGA 320x240 pixels
Frame rate	30 fps (frames per second)
Digital zoom	16x
Video camera settings bar	
Video clip length	Normal, For picture message
Light	Off, Auto
Night mode	Off, On
Self-timer	Yes, same as camera
Effects	Yes, same as camera
White balance	Yes, same as camera
Metering mode	Yes, same as camera
Turn on/off microphone	Off, On
Video camera setup	
Image stabiliser	Off, On
Reset file number	Yes, same as camera
Save to memory	Yes, same as camera

Video telephony

Photo sizes (resolution)	QCIF (176x144 pixels) SQCIF (128x96 pixels)
Digital zoom	16x zoom
Night mode	Yes
White balance	Auto
Brightness	Yes
Video coding	H.263 MPEG-4 Visual Simple Profile Level 0
Audio coding	AMR

Images

Images can be shared using a Bluetooth wireless technology connection, MMS, email message, computer file transfer or memory card.

The image size is limited by the amount of free RAM.

Formats	Details	
JPEG	 ISO/IEC JPEG Baseline DCT Progressive DCT Non-differential nlimited size 	
GIF	 87a, 89a, support for interlacement, animation and transparency Unlimited size 	
ВМР	Windows® bitmap format	
PNG	Unlimited size	
SVG	SVG Tiny 1.2	
WBMP	Wireless bitmapUnlimited size	

Supported character set

Decoding text (Incoming MM	S)	
US-ASCII	UTF-16	
ISO-8859-1	KOI8-R	
ISO-8859-2	GB2312	
Windows-1251	GB 18030	
ISO 10646 (UCS-2)	GB 13000	
UTF-7	BIG-5	
UTF-8		
Coding Text (Outgoing MMS)		
UTF-8		

Short Messaging Service

Feature	Support
SMS Service Centre Number	It is possible to pre-load the SMS Service Centre Number
Pictures	It is possible to insert a picture or an icon into the text message. EMS compliant mobile phones will be able to see the picture correctly
Reply to messages	It is possible to reply to received messages by SMS, MMS, voice message and email
Input methods:	Predictive writing and multitap

Feature	Support
Copy and paste words	Yes
Teaching of predictive words that are not in the predictive dictionary	Yes
Options when creating a message:	
Save a sent message in a "Sent items" folder	Yes
Insert a line in the message	Yes
Assign a validity period to the message	Yes
Use predefined messages	Yes
Options when receiving a message:	
Reply to the sender	Yes
Forward the message	Yes
Save the message on the SIM card	Yes
Get delivery time and date	Yes
Options with the previously sent message:	
Delivery report of the message	Yes (if requested when sending)
Forward the message	Yes
Save the message on the SIM card	Yes
Know the remaining capacity storage	Yes, $>$ 95% full warning, capacity on SIM when saving to SIM
Options with the previously received message:	
Reply to the sender	Yes
Save the message in the inbox	Yes
Forward the message	Yes
Know the remaining capacity storage	Yes, $>$ 95% full warning, capacity on SIM when saving to SIM
Supported ways for replying to a received SMS:	
Via SMS, MMS, voice message, email	Yes
Via phone call (set up a call to the number contained in the message body)	Yes
Via Web browser (go to the Web address contained in the message body)	Yes
Via USSD session	No

Feature	Support
Print via infrared	No
Possibility to enable the user to send a text message to a list of recipients	Yes
Possibility to write an email address as a recipient address	Yes, if email gateway is present
SMS storage	In the phone memory, on the SIM card, or on memory card
Capacity	Up to 1,000 messages
Nokia Picture Messaging	Yes

Enhanced Messaging Service

Enhanced Messaging Service (EMS) according to the standard 3GPP™ TS 23.040 v4.3.0, with the addition of the ODI feature from 3GPP™ TS 23.040 v5.0.0
10
It is possible to: See how many short messages an EMS message consists of before sending it. Choose whether to send the message or not after writing it.
 A signal is heard once all parts of the message have been received or when a time-out occurs. It is possible to re-use the content of an EMS message. Sounds, pictures, and animations can be inserted in a new message, if the object is not protected using ODI.
A receipt is received in the phone when all parts of a concatenated message have been delivered if a delivery report is requested when it is being sent
It is possible to add pictures, animations and sounds to an EMS message
Chimes high, chimes low, ding, tada, notify, drum, claps, fanfare, chords high, chords low
Yes, version 1.2

Feature	Support
Melodies	It is possible to: Receive (always), send using EMS (if not copyright protected). Download melodies and commercial tunes from the Web.
WBMP	Yes
Picture sizes	16x16, 32x32 pixels, variable size in black and white
Pictures	 It is possible to: Edit pictures using PhotoDJ™. Receive (always), send using EMS (if not copyright protected). Download pictures from the Web.
Animations	There is support for the following animations: Angry, Crying, Flirty, Happy, Kiss, Sad, Tongue, Wow, Confused, Devil, Glasses, Indifferent, Laughter, Sceptical and Wink, as defined in 3GPP™ TS 23.040 v4.3.0. It is possible to send and receive animations
TP-PID field value given by the phone before sending an EMS message	0x00
EMS storage capacity	Up to 1,000 messages

Multimedia Messaging Service

Feature	Support
MMS/CSD parameters and MMS/GPRS parameters placement	 MMS is bound to an MMS profile. A MMS profile is bound to a Data account. A data account contains either CSD parameters or GPRS parameters and possibly proxy settings
Possibility to pre-configure the MMS parameters in the factory	MMS/CSD: YesMMS/GPRS: Yes
Possibility to configure the MMS parameters by OTA provisioning	MMS/CSD: YesMMS/GPRS: Yes
Possibility for all the parameters from the parameters set to be OTA provisioned at the same time	MMS/CSD: YesMMS/GPRS: Yes
Possibility for only one parameter, in the set of parameters, to be OTA provisioned	MMS/CSD: NoMMS/GPRS: No
Supplier indication of realized interoperability tests between its MMS User Agent and MMS Relay/Server from other suppliers	Yes

Feature	Support
Support of a standard procedure for OTA provisioning of MMS parameters	OMA Client Provisioning 1.1
Functionalities that the user is able to set during message composition:	 Message subject Message priority Email recipient address Message Cc, Bcc recipient(s) address(es) Delivery report request MSISDN recipient address Validity period
From where can the user insert multimedia elements into multimedia messages:	File Manager Photo album Camera Contacts Calendar Task Note Browser (vBookmark) VideoDJ TM PhotoDJ TM PhotoDJ TM Sound recorder
Possibility for sent messages to be memorised into a folder in phone memory	Yes
Actions that the user can perform after message retrieval:	 Reply to the sender of the message SMS/MMS Reply to the sender and to Cc, Bcc people SMS/MMS Forward the message Delete the message Save message in a dedicated folder Call the sender of a message Save item Mark as unread Details
Multimedia codecs/formats supported for audio	AAC, AMR, MPEG Layer 3, AWB, WAV, MP4, MIDI, iMelody, 3GPP™, XMF, M4A, WMA
Multimedia codecs/formats supported for video	MP4, 3GPP™, SDP, WMV
Multimedia codecs/formats supported for image	JPEG, GIF87, GIF89A, PNG, SVG, WBMP, BMP
Supported formats for message presentation:	 Message body plus attachments (email presentation) SMIL version as described in OMA MMS IOP document version 1.2
Maximum message size that can be handled by the phone	Content Class and Creation mode are applied. Maximum size can also be customised
Maximum number of objects supported in a message	30 objects is standard. It is possible to increase the number through configuration

Feature	Support
Maximum text size	5,000 characters/text
Storage capacity	Up to 500 messages

Email client technical data

Feature	Support
Bearer type (IP)	Yes
Bearer type GSM Data (IP)	Yes, GPRS and HSCSD
Character sets	 ISO: ISO-8859-1, ISO-8859-2, ISO-8859-5, ISO-8859-7, ISO-8859-9, ISO-8859-10, ISO-8859-11 Windows: Windows-1251, Windows-1252, Windows-1254, Windows-1255, Windows-1258 US-ASCII Unicode: UTF-7, UTF-8, UTF-16 Japanese: Shift_JIS, ISO-2022-JP Cyrillic: KOI8-R Simplified Chinese: GB2312, GB18030 Traditional Chinese: Big5
OTA provisioning solution	OMA Client Provisioning 1.1
Protocols	POP3 and IMAP4
Push email	IMAP IDLE (extension of IMAP4 Rev1), OMA Email Notification 1.0 and scheduled checking, Exchange ActiveSync® (EAS)
Secure email	SSL/TLS, both port methods (POPS/IMAPS) and STARTTLS
HTML mail	Yes (tags removed)
Thumbnailed image attachments	Yes
Message management	User selectable inbox size, save messages to Memory Stick, arrange messages by date, size and Email address
ESMTP	Yes
Background sending	Yes

Connectivity

Bluetooth™ wireless technology technical data

Dimension	Support	
Bluetooth [™] wireless technology capability statement	This phone supports Bluetooth Specification, version 2.0 with enhanced data rate (EDR)	
Bluetooth™ wireless technology profiles	Advanced Audio Distribution Profile Audio/Video Remote Control Profile Basic Imaging Profile Dial-up Networking Profile File Transfer Profile Generic Access Profile Generic Object Exchange Profile Handsfree Profile Headset Profile Human Interface Device Profile Object Push Profile Personal Area Networking Profile Phonebook Access Profile Serial Port Profile Synchronization Profile SyncML OBEX binding	
Connectable devices	All products supporting Bluetooth spec. 1.1, or higher, and at least one of the profiles above	
Coverage area	Varies due to radio performance between the connected devices and the occurrence of obstacles. Up to 10 metres (33 feet)	
Transmission power	Class 1, typical +3 dBm or 2 mW	
Frequency band	2.4 GHz - the unlicensed ISM band	
Power consumption	 GSM host processor excluded: Standby, Bluetooth On mode: <0.6 mA Voice to headset (HV3 master): 11 mA (7 mA with EDR functionality, 2EV3 master). Dependent on various parameters such as if the phone is master or slave Data mode average: 27mA at 172.8 Kbps symmetrical (DH1) 	
Data transmission rate	 Data speed at least 800 Kbps on a Dial-up Networking connection (requires access to HSDPA network and may be limited by capacity situation on the 3G base station) Data speed typically 1.0 Mbps on an Object Push connection between two phones (in case of using similar phones and if no other Bluetooth devices are connected) 	

OMA Data Synchronization (SyncML™) technical data

Feature	Support for Sync ML
SyncML compliance	The phone is fully SyncML compliant, having passed SyncML Conformance testing. OMA DS 1.2 or OMA DS 1.1.2 is used depending on configuration and both are supported in Server-alerted synchronization
Basic data formats	Contacts: vCard 2.1, Calendar: vCalendar 1.0 (vEvent) Tasks: vCalendar 1.0 (vTodo) Notes: text/plain, Bookmarks:vBookmark 1.0
Possibility for operators to extend SyncML functionality	The device may be configured to include preset SyncML settings, and to control whether SyncML 1.1 or SyncML 1.2 will be used
Transport method for SyncML messages	HTTP, HTTPS, OBEX (USB, Bluetooth)
Possibility for the user to configure login parameters (for example, username and password) to access the remote database	Yes
Configuration parameters that can be entered/modified by the user	Server URL, Username, User PWD, Paths to databases (Calendar, Contacts, Notes, Tasks and Bookmarks), UserID and PWD for databases, Databases to be synchronised (On/Off), Internet profile, Synchronization interval, Server ID and Server PWD, permission to allow server-alerted synchronization and roaming options. Can be provisioned with OMA Client provisioning v1.1 and OMA Device Management v1.2
Ability to deal with multiple servers	Yes
Ability to perform conflict resolution actions	Yes

Microsoft® Exchange ActiveSync®

Feature	Support for Exchange ActiveSync
Protocol version	The phone supports version 2.5 of Microsoft Exchange ActiveSync
Supported applications	Email, Calendar, Phonebook
Transport method used	HTTP, HTTPS
Possibility for the user to configure login parameters for remote server	Yes

Feature	Support for Exchange ActiveSync
Configuration parameters that can be entered/modified by the user	Server URL, username, domain name, password, applications to sync, email message size, email attachment size, email date range, message alert sound, calendar date range, interval sync, secure connection, roaming option
Ability to perform conflict resolution	No

Web browser technical data

Feature	Support in the browser
Bookmarks	Yes, with folders and sorting supported
Bookmark Export/Import	Yes, can be sent and received using vBookmark format using Bluetooth™ wireless technology, SMS, MMS and email
Browser compliancy	The Web browser is compliant with the following standards: HTML ver. 4.01 XHTML™ Basic 1.0 XHTML™ 1.1, Module-based XHTML™ XHTML™ Mobile profile WML 1.3 Cascading Style Sheets, level 2 revision 1, CSS 2.1 Specification Wireless CSS Specification, Version 26-Oct-2001 (WAP-239-WCSS-20011026-a) ECMA-script according to specifications found at http://www.ecma-international.org/publications/standards/ Stnindex.htm ECMAScript Mobile Profile AJAX Document Object Model Level 2 (DOM 2) Scalable Vector Graphics, Mobile SVG Profile: SVG Tiny, version 1.2 For further details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/
Browser version	Access NetFront 3.4
Cache	Yes (size 2 MB)
Character sets *	Most standard character sets, among others UTF-8 (Default), UTF-16, USASCII, Latin1, UCS2. For updated and detailed information, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/ * When creating pages, it is recommended to always save the page contents as UTF-8.
Clear cache	Yes, persistent. By user interaction, at SIM card change or master reset
Frames	Full Frame support: Frames, IFrames

Feature	Support in the browser
Image formats and animations	GIF (interlaced and non-interlaced) WBMP, JPEG, PNG, BMP and SVG. Animated GIFs, animated SVG and Flash
Schemes	Http:, https:, rtsp:, mailto:, smsto:, mmsto:, tel:, wtai:
Streaming	Progressive download, RTSP, Java script controls
Web feeds	Ticker, podcasts, enclosures, OPML import. No support for ATOM
User agent profile	
User Agent Profiles	Yes, list of client characteristics - for example, screen size. For details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/
URL sent pointing to the UA profile at the beginning of browser session	Yes. For details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/
Download	
OMA download functionality	Yes
HTTP GET solution to download content/ Uses browser for download	Yes
Other download content	Yes. No download limit when using HTTP protocol
Download application/product memory check	Yes
Downloaded object solution	Yes. The user is informed where the content is saved and asked if it should be used at once or later
UAP indication for downloading	Yes
Other features	Yes. Save, delete, forward, use, manage
Object formats	All formats can be downloaded and saved, but only formats supported by the phone can be used by the phone
Resume	Yes
Background download	Yes
Progressive download	Yes
Streaming	Yes
Browser navigation	
Selection keys	Yes. Two selection keys and centre navigation key
Search from standby	Yes. Enter address, search the web or bookmarks.
Separate/dedicated back or erase keys	Yes

Feature	Support in the browser
Display backlight on when browsing	Yes
Predictive writing	Yes
"http://" string displayed automatically when entering URLs	Not displayed but the "http://" is added automatically to the URL
"www" added automatically when entering URLs	Yes
Combined Search/Go To input field	Intelligent input field changes appearance (Search or Go to) depending on user input. "www", ".com" and other URL syntax can be used to trigger the Go To appearance
Internet network features	
Bluetooth™ wireless technology (as local connection)	Yes
Infrared (as local connection)	No
Network settings	Yes
PPP Authentication	PAP, CHAP supported
Security	HTTPS authentication TLS version 1 SSL version 3 WIM on SIM ICC X.509 certificate support, Mobile Profile WPKI OTA download of trusted certificates
USB (as local connection)	Yes
PUSH	
Content types	
Service Indication (SI)	Yes
Service Loading (SL)	Yes
Cache Operation (CO) content type	No
Session Initiation Application (SIA)	Yes
Man Machine Interface	
SI/content retrieval postponing	Yes
SI menu structure accessibility	Messaging, Inbox
SL reception warning	The user can make a choice if a dialogue is wanted or not before loading the SL

Feature	Support in the browser
SIA reception warning	Yes
Cache size limitations	The oldest push in the inbox will be discarded
Number of push messages	Depends on the size of the push messages. Around 20 push messages with a size of 1024 bytes URL and 1024 bytes Indications for Service Indication can be saved.
Push deactivate	Yes
Dynamic push menu changes	No. There are no changes in the menus when activating/deactivating push
Security	
Mechanisms for push	None
Trust with PPG	Sending a SIA is the most reliable
WSP push sessions	No
HTTP push sessions	The White List (a setting to allow push messages only from certain addresses) is supported for IP address
SMS connection-less push	The White List (a setting to allow push messages only from certain addresses) is supported for SMS Center
Denial of service/spoofing	Setting to select when to allow push messages: Always, always ask or never. There is also a setting to select whether to allow push messages from all senders or only from certain addresses (the White List)

Client Provisioning

Feature	Support
Provisioning types	OMA Client Provisioning (v1.1)
Total Parameter sets	25 (shared between the provisioning types) < or = 25 (total number of data accounts)
Parameter set list	See the <i>Device</i> Management v4 Developers Guideline at Developer World http://www.sonyericsson.com
Factory pre-configuration	Yes. This also provides the possibility to lock a setting
Security mechanism	
Bearer	

Feature	Support
SMS	Uses security mechanism (SEC) methods according to OMA-WAP-ProvCont- v1_1-20050428-C (see www.openmobilealliance.o rg). For NETWPIN the user is asked to accept to install received settings. For USERPIN, USERNETWPIN and USERPINMAC the user is subsequently asked to enter a PIN code that is a shared secret between the service provider and the user
Carrier reset/provisioning	Yes, but not if the set is pre-configured in the factory and locked
SWIM	Not used for provisioning. The SWIM is only used for wireless security, both SSL/TLS connections and digital signatures
Applicative provisioning	
Preferred bearer customization	Yes
Other applications/features	Yes (MMS, Email, OMA Data Synchronization, Wireless Village, OMA Device Management, Streaming)
Technologies	
OMA Client Provisioning	Yes, Client Provisioning version 1.1
Nokia/Ericsson OTA	No
Openwave OTA	No
Other	No
Provisioning bearer	SMS

Abbreviations

ЗGPPTM

3rd Generation Partnership Project

AAC

Advanced Audio Coding

AAC+

High Efficiency AAC v.1

AJAX

Asynchronous JavaScript and XML

AMR

Adaptive Multi Rate. Audio format for speech sounds

AMR-NB

Adaptive Multi Rate Narrow Band

AMR-WB

Adaptive Multi Rate Wide Band, a more advanced codec that supports speech with higher quality

API

Application Programming Interface

Bluetooth PAN

Bluetooth Personal Area Network

CS

Circuit Switched

CSD

Circuit Switched Data

DRM

Digital Rights Management. Controlling copying and distribution of contents, with respect to intellectual property rights

DTMF or Touch Tone

Dual Tone Multi-Frequency signal. Codes sent as tone signals. Used for telephone banking, accessing an answering machine, etc.

EDGE

Enhanced Data Rates for GSM Evolution

e-GSM

Extended GSM. New frequencies specified by the European Radio Communications Committee (ERC) for GSM use when additional spectrum is needed (network-dependent). It allows operators to transmit and receive just outside GSM's core 900 frequency band. This extension provides increased network capability

eAAC+

High Efficiency AAC v.2

EDR

Enhanced Data Rate

EFR

Enhanced Full Rate, speech coding

EMS

Enhanced Messaging Service. Allows the user to add simple pixel pictures and animations, sounds and melodies to a text message. The EMS 3GPP™ standard also includes text formatting

ETSI

European Telecommunications Standards Institute

FM

Frequency Modulation of the (radio) carrier wave

FR

Full Rate, speech coding.

GIF

Graphics Interchange Format

GPRS

General Packet Radio Services

GSM

Global System for Mobile Communications. GSM is the world's most widely used digital mobile phone system, now operating in over 100 countries around the world, particularly in Europe and Asia-Pacific.

The GSM system family includes GSM 850, GSM 900, GSM 1800 and GSM 1900. There are different phases of roll-out for the GSM system and GSM phones are either phase 1 or phase 2 compliant

HR

Half Rate, speech coding

HSCSD

High Speed Circuit Switched Data

HSDPA

High Speed Downlink Packet Access

HTML

HyperText Markup Language

HTTP

HyperText Transfer Protocol

JPEG

Joint Photographer Expert Group

MIDI

Musical Instrument Digital Interface

ME

Mobile Equipment

MP

Megapixel

MP3

Short for "MPEG-1/2/2.5 layer 3", an audio coding scheme

MPEG/MPG

Moving Picture Experts Group

MT

Mobile Termination

ODI

Object Distribution Indicator

OMA

Open Mobile Alliance

OTA

Over The Air

PDA

Personal Digital Assistant

PDP

Packet Data Protocol

PIM

Personal Information Management

PNG

Portable Network Graphic

QCIF

Quarter Common Intermediate Format

RDS

Radio Data System

RSS

Really Simple Syndication

RTSP

Real Time Streaming Protocol

SI

Service Indication

SL

Service Loading

SIM card

Subscriber Identity Module card – a card that must be inserted in any GSM-based mobile phone. It contains subscriber details, security information and memory for a personal directory of numbers. The card can be a small plug-in type or credit card-sized, but both types have the same functions. The phone uses the small plug-in card.

SMS

Short Messaging Service. Allows messages of up to 160 characters to be sent and received via the network operator's message centre to a mobile phone

SP-MIDI

Scalable Polyphony MIDI

SS

Supplementary Services

SSL

Secure Socket Layer

TLS

Transport Layer Security

TTI

Transmission Time Interval

UI

User Interface

UMTS

Universal Mobile Telecommunications System

URL

Uniform Resource Locator.
The global address of documents and other resources on the World Wide Web

USSD

Unstructured Supplementary Services Data

vCard

vCard automates the exchange of personal information typically found on a traditional business card, for use in applications such as Internet mail, voicemail, Web browsers, telephony applications, call centres, conferences, PIMs /PDAs, pagers, fax, office equipment and smart cards. vCard is specified by IETF

VGA

Video Graphics Array

WAV

Waveform audio format

WMA

Windows Media Audio

WMA Pro

Windows Media Audio Professional

WBMP

Wireless BitMap.
A graphic format optimised for mobile computing devices

WCDMA

Wideband Code Division Multiple Access

WML

Wireless Markup Language. A markup language used for authoring services, fulfilling the same purpose as HyperText Markup Language (HTML) does on the World Wide Web (WWW). In contrast to HTML, WML is designed to fit small handheld devices

WWW

World Wide Web

XHTML

Extensible HyperText Markup Language

XML

Extensible Markup Language

Related information

Documents

- Sony Ericsson User guide
- Sony Ericsson FAQ

- AT Command Reference Manual
- WAP 2.0 Specifications

Links

- www.sonyericsson.com/
- www.ericsson.com/mobilityworld/
- www.midi.org
- www.extendedsystems.com
- www.gsmworld.com/
- www.bluetooth.com
- www.imc.org
- www.3gpp.org
- www.irda.org

- www.etsi.fr
- www.openmobilealliance.org
- www.imc.org/pdi/
- www.w3.org/TR/xhtml-basic/
- www.java.sun.com
- www.memorystick.org/
- www.memorystick.com/
- www.sonyericsson.com/updateservice
- www.sonyericsson.com/support

Trademarks and acknowledgements

The Bluetooth™ word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Sony Ericsson is under licence.

The Liquid Identity logo, PlayNow, BestPic, SensMe, VideoDJ, MusicDJ, TrackID and PhotoDJ are trademarks or registered trademarks of Sony Ericsson Mobile Communications AB.

Mega Bass, Memory Stick Micro, Cyber-shot, M2, Smile Shutter™ and Sony are trademarks or registered trademarks of Sony Corporation.

NetFront is a trademark or a registered trademark of ACCESS Co., Ltd.

PictBridge is a trademark or registered trademark of Canon Kabushiki Kaisha Corporation.

Ericsson is a trademark of Telefonaktiebolaget LM Ericsson.

TrackID™ is powered by Gracenote Mobile MusicID™. Gracenote and Gracenote Mobile MusicID are trademarks or registered trademarks of Gracenote, Inc.

Google™ and Google Maps™ are trademarks or registered trademarks of Google, Inc.

MicroSD™ and Transflash™ are trademarks or registered trademarks of SanDisk Corporation.

The IrDA Feature Trademark is owned by the Infrared Data Association and used under licence there from.

XHTML[™] is a registered trademark of the W3C.

Microsoft®, Windows® Vista, Windows Media and ActiveSync are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Adobe Flash Lite are trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

3GPP™ is a trademark of ETSI in France and other jurisdictions.

SyncML is a trademark or registered trademark of Open Mobile Alliance Ltd.

PlayNow is not available or supported in all markets or regions.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. End-user license agreement for Sun Java[™] J2ME[™]:

- 1. Restrictions: Software is confidential copyrighted information of Sun and title to all copies is retained by Sun and/or its licensors. Customer shall not modify, decompile, disassemble, decrypt, extract, or otherwise reverse engineer Software. Software may not be leased, assigned, or sub licensed, in whole or in part.
- 2. Export Regulations: Software including technical data, is subject to U.S. export control laws, including the U.S. Export Administration Act and its associated regulations, and may be subject to export or import regulations in other countries. Customer agrees to comply strictly with all such regulations and acknowledges that it has the responsibility to obtain licenses to export, re-export, or import Software. Software may not be downloaded, or otherwise exported or re-exported (i) into, or to a national or resident of, Cuba, Iraq, Iran, North Korea, Libya, Sudan, Syria (as such listing may be revised from time to time) or any country to which the U.S. has embargoed goods; or (ii) to anyone on the U.S. Treasury Department's list of Specially Designated Nations or the U.S. Commerce Department's Table of Denial Orders.
- 3. Restricted Rights: Use, duplication or disclosure by the United States government is subject to the restrictions as set forth in the Rights in Technical Data and Computer Software Clauses in DFARS 252.227-7013(c) (1) and FAR 52.227-19(c) (2) as applicable.

All other trademarks and copyrights are the property of their respective owners.